



G29 Solvent Gloves

Codes: 49822, 49823, 49824, 49825, 49826, 49827

Product Information

Code	Size	Palm Width* Unit: in	Glove Length* Unit: in	Quantity
49822	6/XS	3.03	11.6	50 gloves/carton; 10 cartons/case
49823	7/S	3.27	11.6	50 gloves/carton; 10 cartons/case
49824	8/M	3.74	11.6	50 gloves/carton; 10 cartons/case
49825	9/L	4.17	11.6	50 gloves/carton; 10 cartons/case
49826	10/XL	4.41	11.6	50 gloves/carton; 10 cartons/case
49827	11/XXL	4.65	11.6	50 gloves/carton; 10 cartons/case

*ASTM D3578; EN455-2; EN420



Property	Description
General Product Information	Product is classified as Category III PPE according to EC Council Directive 89/686/EEC; 3 year expiration date
General Description	Neoprene blend glove, powder free, non-sterile, textured fingertip, ambidextrous gloves, beaded cuff, double chlorination, blue on outside, white on donning side, silicone free as tested by FTIR

Physical Property	Result	Test Method (0.65 AQL)
Watertightness	Pass	ASTM D 5151; EN 455-1; EN 374-1; EN374-2
Airtightness	Pass	ASTM D 5151; EN 455-1; EN 374-1; EN374-2

Thickness	Target	Test Method (2.5 AQL)
Palm	9.0 mil (0.23 mm)	ASTM D6319
Middle Finger	12.6 mil (0.32 mm)	ASTM D6319

Property	Target	Testing Method (2.5 AQL)
Tensile Strength -Before Aging	15.75 Mpa	ASTM D 412
Tensile Strength - After Aging	22.50 Mpa	ASTM D 573
Ultimate Elongation – Before Aging	612%	ASTM D 412
Ultimate Elongation – After Aging	537%	ASTM D 573

Property	Performance Level	Test Method
Abrasion resistance	Level 2	EN 388:2003
Dexterity	Level 5	EN 420:2003

For Chemical Break Thru and Permeation Data, please refer to the Chemical Resistance Guide. To request contact KCPInfo@kcc.com

Workmanship Requirement: Gloves shall be made in accordance with reasonable industry practice with respect to defects, dirt and contamination. Gloves should be packaged as specified having described size and color in the appropriate quantity as listed. Shipping Case and inner packaging shall be labeled with product name, size, lot / batch and catalog number. For additional information: 1-888-346-GOKC or KCPInfo@kcc.com

Kimberly-Clark warrants that its products (1) comply with K-C's standard specifications as of the delivery date to K-C's authorized distributors/direct purchasers and are warranted for the following periods from end user's date of purchase (verified by valid sales receipt) (a) five years for Balder Technology auto darkening filters; (b) two years for all other auto darkening filters; and (c) one year for powered air purifying respirators; (2) comply with all K-C labeling representations; and (3) are manufactured in compliance with all applicable federal, state, and local laws in effect at the time and place of manufacture of the products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. K-C is not liable for any kind of special, incidental, or consequential damages. K-C's liability for breach of contract, tort or other cause of action shall not exceed the product purchase price. Purchasers and users are deemed to have accepted the above warranty and limitation of liability, and cannot change the terms by verbal agreement or by any writing not signed by K-C. To the extent required by applicable law, K-C does not limit its liability for death/injury resulting from K-C's negligence.



Exceptional Workplaces

Pub: Feb 2015