101911

JET® S90 Series hand chain hoists were designed with reliability and durability to perform in light-duty industrial applications. Easily maintained and serviced, the JET® S90 is available in capacities from ½ ton to 10 ton and standard lifts of 10, 15, 20, and 30 feet (custom lifts available). The JET® S90 is the ideal contractor grade hoist.



### **FEATURES**

- Safety
- Weston Style Dual Pawl Brake System- Double pawl design increases
- Alloy Steel Hooks- Industrial rated hooks rotate 360 degrees for easy rigging. Hooks slowly stretch to indicate an overload situation increasing jobsite
- Durability
- Needle Bearing Design- Promotes long hoist life with low wear reducing
- Heat Treated Load Plates- Heat treated, case hardened and corrosive resistant coated internal parts extend the life of the hoist in the harshest of
- Grade 80 Load Chain- Grade 80 black oxide coated load chain for durability
- All Steel Construction-Impact resistant covers that provide durability and
- Compact Design- Smaller body and lightweight design for low headroom applications and use in confined areas
- Industry- Complies with OSHA Regulations, ANSI / ASME B30.16 and HST-2 Standards
- · Certification- Load tested to 125% of capacity with certificate



#### JET RED ASSURANCE LIFETIME WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK



101911

### **SPECIFICATIONS**

Load Capacity (Tons)	1
Lift (Ft.)	15
Overload Protection	No
Headroom (In.)	12
Hand Chain Overhaul (Ft.) to Lift Load 1Ft.	53
Hand Chain Pull Force (LRF) to Move Load	60





101911

#### **FULL SERIES**

FULL SERIES							
STOCK NO	MODEL NO	LOAD CAPACITY (TONS)	LIFT (FT.)	OVERLOAD PROTECTION	HEADROOM (IN.)	HAND CHAIN OVERHAUL (FT.) TO LIFT LOAD 1FT.	
101900	S90-050- 10	1/2	10	No	11	32	
101901	S90-050- 15	1/2	15	No	11	32	
101902	S90-050- 20	1/2	20	No	11	32	
101903	S90-050- 30	1/2	30	No	11	32	
101910	S90-100- 10	1	10	No	12	53	
101911	S90-100- 15	1	15	No	12	53	
101912	S90-100- 20	1	20	No	12	53	
101913	S90-100- 30	1	30	No	12	53	
101920	S90-150- 10	1-1/2	10	No	14-1/2	57	
101921	S90-150- 15	1-1/2	15	No	14-1/2	57	
101922	S90-150- 20	1-1/2	20	No	14-1/2	57	
101923	S90-150- 30	1-1/2	30	No	14-1/2	57	
101930	S90-200- 10	2	10	No	17-1/2	71	
101931	S90-200- 15	2	15	No	17-1/2	71	
101932	S90-200- 20	2	20	No	17-1/2	71	
101933	S90-200- 30	2	30	No	17-1/2	71	
101940	S90-300- 10	3	10	No	20-1/2	115	
101941	S90-300- 15	3	15	No	20-1/2	115	
101942	S90-300- 20	3	20	No	20-1/2	115	
101943	S90-300- 30	3	30	No	20-1/2	115	
101950	S90-500- 10	5	10	No	23-1/2	178	
101951	S90-500- 15	5	15	No	23-1/2	178	



101911

#### **FULL SERIES**

STOCK NO	MODEL NO	LOAD CAPACITY (TONS)	LIFT (FT.)	OVERLOAD PROTECTION	HEADROOM (IN.)	HAND CHAIN OVERHAUL (FT.) TO LIFT LOAD 1FT.
101953	S90-500- 30	5	30	No	23-1/2	178
101960	S90-1000- 10	10	10	No	30	357
101961	S90-1000- 15	10	15	No	30	357
101962	S90-1000- 20	10	20	No	30	357
101963	S90-1000- 30	10	30	No	30	357

