JAT-630, 3/8" REVERSIBLE ANGLE

505630

Rated to last for those demanding 12 hour days, the R12 Series air tools are built to tackle the most extreme jobs. Engineered for Overtime, these tools feature the superior strength and durability needed across a wide range of applications.



FEATURES

- · Industrial Jacobs's keyed chuck efficiently transfers torque when needed
- · Low profile angled head for work in tight spots
- Ergonomically designed grip absorbs vibration and reduces hand fatigue
- · Bottom-mounted, forward/reverse switch locks in place
- Variable-speed trigger for precise speed control
- Rugged, ball-bearing design for durability
- Head rotates 360° for increased versaility in awkward applications
- Performace @ 90 PSI. Air Inlet NPT 3/8". Min Hose Size 3/8"



RED ASSURANCE LIFETIME WARRANTY

We are confident of every Air Tool we manufacture. To prove it, we back every Air Tool that bears the JET name with a Lifetime Warranty. The JET Lifetime Warranty covers manufacturer's defects, but does not cover misuse, abuse, accidents, negligence, wear and tear, improper repair or alternations.



1 YEAR 'WEAR & TEAR' COVERAGE

JET covers all Air Tool repair costs including parts and labor for the first year of ownership. Proof of purchase is required. JET's 'Wear & Tear' Coverage does not cover misuse, abuse, accidents, negligence, improper maintenance, repair or alterations.

STAND BEHIND YOUR WORK



JAT-630, 3/8" REVERSIBLE ANGLE

505630

SPECIFICATIONS

Classification	R 12
Spindle Thread (In./TPI)	3/8"-24
Chuck Size (In.)	3/8
Free Speed (RPM)	1,200
Horse Power (HP)	0.5
Air Inlet (NPT/In.)	1/4
Air Hose (ID/In.)	3/8
Air Pressure (PSI)	90
Air Consumption (CFM)	4
Sound Pressure (db) (A)	90
Sound Power (db) (A)	97
Vibration Value (m/s²)	0.5
Overall Length (In.)	8
Weight (Lbs.)	2.78



STAND BEHIND YOUR WORK™



JAT-630, 3/8" REVERSIBLE ANGLE

505630

FULL SERIES

STOCK NO	MODEL NO	CLASSIFICATION	SPINDLE THREAD (IN./TPI)	CHUCK SIZE (IN.)	FREE SPEED (RPM)	HORSE POWER (HP)
505621	JAT-621	R 12	3/8"-24	1/2	800	0.5
505620	JAT-620	R 12	3/8"-24	3/8	1,800	0.5
505630	JAT-630	R 12	3/8"-24	3/8	1,200	0.5

