

MARINE PRODUCTS

MARINE

MARINE

MARINE

MARINE

MARINE

MARINE KOPR™ Copper Anti-Seize Compound Conforms to Military Specification MIL-PRF-907E

MARINE KOPR is a specially formulated marine anti-seize compound in a water-resistant aluminum complex base grease with rust and corrosion inhibitors to minimize the harsh environmental conditions in which it is used. Stops rust, corrosion, heat freeze, galling, etc. while lowering overall maintenance costs. Ideal for engine room applications.



Brushable: 0°F (-18°C) to 1800°F (982°C)
Service Rating: -65°F (-54°C) to 1800°F (982°C)
Packaging: Half and one pound brush top cans
Product Codes: 09702, 09704

MARINE MOLY™ Molybdenum Disulfide Paste Marine Lubricating Paste and Aerosol



Contains a high concentration of molybdenum disulfide in paste or aerosol form, which "plates" metal surfaces. Provides a low-friction shield in a variety of applications such as on highly loaded gears, open spur gears, marine transmission gears, etc., while adhering tenaciously to all metal surfaces. MARINE MOLY has a 300,000 psi film strength, is extremely water resistant and may be applied to hot surfaces. MARINE MOLY can be used as a running-in (break-in) lubricant, assembly lubricant and general purpose metal working lubricant requiring high load-carrying performance.

Service Rating: -300°F (-184°C) to 750°F (399°C) - Paste to 300°F (149°C) - Aerosol
Packaging: 1 pound plug top can and 12 ounce aerosol can
Product Codes: 65005, 65041

MARINE WRL™ (Wire Rope/Chain Oil) ISO 22 Contains no 1.1.1 Trichloroethane or SARA Listed Ingredients

MARINE WRL produces longer rope and chain life, reduces down time and is easily pumpable at temperatures as low as -25°F (-32°C). Specially formulated to permeate or penetrate to the core, ensuring lubrication throughout while providing a nondrying, nontacky film on the outside of the rope to protect from rust and corrosion, as well as lubricating drums and sheaves. MARINE WRL remains flexible in extreme weather conditions, eliminating flaking and peeling, dirt pickup and lubrication sling-off. MARINE WRL can be used to lubricate all sizes of wire rope, chains, leaf springs, etc. Application may be by hand, automatic lube system or aerosol can. Color - clear amber. USDA H-2 Authorized for food processing.

Service Rating: -25°F (-32°C) to 350°F (175°C)
Packaging: 1 and 5 gallon pails, 15 and 50 gallon drums
Product Codes: 66020
Note: Aerosol available - see Industrial WRL™ (code #34041)

MARINE MULTIPURPOSE #2 GREASE with EP Additives

A versatile soap grease. Extremely water resistant. Contains EP additives for protection from salt water, salt spray, rust and corrosion. Smooth texture, heavy body with excellent pumpability even in extreme conditions. Two hundred fifty (250) weld point on 4-Ball Weld (ASTM D-2596), NLGI Grade 2 grease and dropping point of 350°F (175°C). Color - purple.



Service Rating: 0°F (-18°C) to 325°F (163°C)
Packaging: 14 ounce cartridge, 35 pound pail
Product Codes: 63050, 63016

RUST GUARD™ Rust and Corrosion Inhibitor Exceeds Military Specifications MIL-C-16173D & MIL-3-23411A



RUST GUARD provides long-term, heavy duty protection from rust and corrosion on metal marine parts, tools, equipment, pipe, valves, fittings and related equipment for up to twenty-four months. RUST GUARD forms a tough, durable, dry, waxy film that dries to the touch in two to three hours and is the ideal product to protect against the effects of water, humidity or salt spray. RUST GUARD is blue in color, easily applied by brush, spray or aerosol application and can only be removed by using safety solvent/degreaser similar to JET-LUBE's CLEAN-UP™. RUST GUARD contains no 1.1.1

Trichloroethane or SARA listed ingredients and is both environmentally and ozone safe. NSF Registered.

Packaging: Aerosol, 1 and 5 gallon pails and 50 gallon drum
Product Codes: 13241, 13233, 13235, 13229

JET-LUBE® SHEEN-FREE™ Biodegradable Wire Rope Preservative/Lubricant

SHEEN-FREE protects wire rope from external surface corrosion and penetrates the inner strands to lubricate and reduce friction. SHEEN-FREE is a preservative and lubricant that is NONHAZARDOUS, BIODEGRADABLE AND NONSHEENING, ideally suited for the marine industry. Develops a protective film that is soft, flexible, tack-free and resists dust and dirt buildup. SHEEN-FREE's formula exceeds USCG specifications. Can be applied by swabbing, brushing or spraying directly onto the cable. Recommended for standing and running rigging where flexibility and performance is required. Also protects bright/black wire, stainless steel and galvanized cables.

Packaging: 5 gallon pail and 15 and 50 gallon drums
Product Codes: 33720, 33724, 33729

CORPORATE LOCATIONS Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com

WIRE ROPE and HAWSER GREASE

White, International Grade, NLGI Grade 2

Conforms to US Military Specification MIL-PRF-18458 C (SH)



WIRE ROPE and HAWSER GREASE is a high performance, white grease that is excellent for the lubrication of critical marine wire rope applications such as shipyard gantry cranes, mast hoisting cables, loading cranes, offshore rig anchor cables and hawser lines. Nondrying, nonstaining film protects outer strands from corrosion while lubricating inner strands, drums and sheaves.

Service Rating: 0°F (-18°C) to 325°F (163°C)

Packaging: 35 pound pail, 120 and 400 pound drums

Product Codes: 34516, 34524, 34529

Z-PLATE™ Zinc-Rich Galvanize Cold Galvanizing Compound

Fights rust and corrosion with galvanic action equal to that of hot-dip galvanizing. Z-PLATE is not a paint, but a 95% pure zinc compound that forms a tough, durable and flexible zinc metal coating, which bonds electro-chemically with the base metal to provide long-term protection. Excellent for marine, offshore drilling and related industries. Meets Military Specification MIL-PRF-26915D (USAF).

Packaging: 14¾ ounce aerosol can

Product Code: 60541



769 LUBRICANT® and Penetrant

The Multipurpose Product for Marine Use

769 LUBRICANT is the ideal lubricating, penetrating, moisture displacing and rust/corrosion preventive product available today. Unequaled where salt water, salt spray or other harsh environments are encountered. Restores life to nylon rope. 769 LUBRICANT gives total performance while being free of 1.1.1 Trichloroethane or SARA listed ingredients. Product is a light machine oil base that is chemically stable, nonflammable and nonevaporative. Aerosol uses safe CO₂ propellant. Marine application include winches, shackle pins, toggle pins, sheaves, swivels, capstans, wiring harnesses, spark plugs, etc. Meets or exceeds Military Specifications MIL-C-23411A and VV-P-216B. Thirty-five (35) KV dielectric strength. Color - clear amber. NSF H-2 Registered for food processing.

Packaging: 12 ounce aerosol can, 16 ounce spray bottles, 1 and 5 gallon jugs, and 50 gallon drum

Product Codes: 37341, 37343, 27533, 27535, 27529



WLD™ Wire Rope, Cable Chain Lubricant Contains Molybdenum Disulfide (MoS₂)

WLD is a highly adhesive, water resistant lubricant and dressing containing rust and corrosion inhibitors that prevents moisture from penetrating wire lines, ropes, cables and sheave grooves. Impervious film does not attract dust or dirt. Ideal lubricant for cables and chains in salt water environments. May be applied by aerosol or brush.

Service Rating: -55°F (-48°C) to 300°F (149°C)

Packaging: 12 ounce aerosol can, 35 pound pail, 120 and 400 pound drums

Product Codes: 28541, 28516, 28524, 28529



#202 MOLY-LITH™

Multipurpose Grease

Contains Molybdenum Disulfide (MoS₂)

Contains micro-fine molybdenum disulfide (MoS₂) particles to further enhance load-carrying and low friction characteristics of this 12-hydroxy lithium grease. Provides unequaled protection wherever dirt, dust, humidity, rain and adverse temperatures are critical problems. NLGI Grade 2; blue/black in color.

Service Rating: 0°F (-18°C) to 300°F (149°C)

Packaging: 14 ounce cartridge, 1 and 5 pound cans, 35 pound pail, 120 and 400 pound drums

Product Codes: 33050, 33005, 33006, 33016, 33024, 33029



CLEAN-UP™

Degreaser/Safety Solvent

A heavy duty, no foaming, chlorinated solvent that rapidly dissolves oil, grease, paint, tar and grime on contact leaving a clean, residue free finished surface. CLEAN-UP is a nonacid, alkali-free product that will not corrode or damage metal surfaces. Apply full strength in a well ventilated area. Safe, nonconductive 29 KV dielectric strength. Ideal for use on appliances, bearings, cables, cement, chains, engine parts, gears, injectors, machinery metal, motors and tools. CLEAN-UP is NSF K-1 Registered for use in Federally Inspected Meat and Poultry Plants. Nonflammable.

Packaging: 18 ounce aerosol, 1 and 5 gallon

Product Code: 61542, 61533, 61535



ALCO-EP-73 PLUS™

Water Resistant, Multipurpose Grease

Conforms to Military Specification MIL-PRF-18458 C (SH)

Extremely water resistant aluminum complex based grease contains inorganic EP and anti-wear additives for use where tolerances are low and/or speeds and loads are high. Ideal for sub sea application. Extremely rust and corrosion resistant grease, performs well over a wide temperature range. NLGI Grade 2, red in color.

Service Rating: -25°F (-32°C) to 450°F (232°C)

Packaging: 14 ounce cartridge, 35 pound pail, 120 and 400 pound drums

Product Codes: 37750, 37716, 37724, 37729



WHITE ICING™

Sheen Free Ship & Barge Launching Grease

A state-of-the-art, sheen free, biodegradable ship launching grease that replaces the cumbersome 2-part process products. It's brushable consistency is easy to apply and the balanced package of boundary lubricants make this product a must-use item.

Packaging: 5 gallon pail, 15 gallon keg and 50 gallon drum

Product Codes: 23616, 23624, 23629