



SPECIFICATION SHEET

262-AEJ030

SUREFIT™ CONTOUR CAP MOUNTED EAR MUFFS

- Easy to attach and detach from helmet
- Spring loaded arms provide an excellent fit to the ear
- Soft foam ear cushions ensure comfortable wear
- Durable polystyrene ear cups pivot and slide for a secure seal
- NRR of 21 dB for protection against common industrial noise
- Conforms to ANSI S3.19-1974 & EN352-1

APPLICATIONS

- Airports
- Excavation Equipment
- Generators
- High Frequency Welders

CARE INSTRUCTIONS

The ear muffs may be cleaned with soap and warm water and dried with a soft cloth. The ear muffs should not be cleaned with chemical nor abrasive cleaners. Store out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

INSTRUCTIONS FOR USE

Fit ear muffs to the Industrial Safety Helmet as per the instructions supplied. Position the ear muff cups at the bottom of the slots in the arm. Fit helmet on head and tighten to ensure correct fit. Adjust cups until comfortably seated over each ear.

Limitations of Use:

Protection will only be offered if the ear muff and the unit are fitted correctly. Ear pads may deteriorate with use and should be examined at frequent intervals. Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer. The ear pads, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice.

Notes:

- If the ear muff is to be worn for long periods the noise level must be reduced to 85dB. Before selection of a suitable ear muff a noise survey should be carried out.
- Spectacle frames and hair between the ear pads and the head may affect the performance of the ear muff.

TECHNICAL DATA

MATERIAL	Ear Muffs: High Impact Polystyrene Cups; Nylon Arms; Polypropylene Housing & Fittings; Steel Inner Fittings; PVC Flexible Coupling Open Cell Foam Inserts: PVC Covered Foam Cushioning
COLOR	■ Blue / ■ Black
NRR	21 dB
SNR	26 dB
STYLE	Cap Mounted
SIZE	One size fits all
DIMENSIONS	Ear Muff Cup Open Area: 44 mm x 65 mm / 1.73 in x 2.56 in
PACKAGING	1 pair per polybag; 50 per case
WEIGHT	0.21 kg / 7.4 oz.
CASE WEIGHT	23.1 lbs / 10.5 kg
COO	China



BARCODES

ITEM	EACH	CASE
■ 262-AEJ030-50	5038428120470	5038428811453

EPA / ATTENUATION DATA

FREQUENCY HZ	125	250	500	1000	2000	3150	4000	6300	8000	NRR	SNR
Mean Attenuation dB	15.6	16	24.7	31.5	33.3	42.2	40.4	41	39.8	21 dB	26 dB
Group Attenuation dB	31.7				172.2			80.8			
Standard Deviation dB	3.5	2.1	2.8	3.3	3.2	3.5	3.7	4.9	4.5		

Tested in accordance with ANSI standard S3.19-1974

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.